



CRI

90+



CCT




360° Rotation



90° Tilt

Features

- IC Rated
- Airtight
- Dimmable
- Work with most of existing dimmer in market
- Five years limited warranty
- Not for emergency lighting
- Suitable for damp locations



Technical Specifications

Model No.:	Round: VO-RMD4W9-120-D-5WAY/WH VO-RMD4W9-120-D-5WAY/BK Square: VO-SMD4W9-120-D-5WAY/WH VO-SMD4W9-120-D-5WAY/BK
Nominal Wattage(W)	9W
Lumens Delivered(LM)	800
Equivalency	60W INC
Efficiency(LM/W)	88
Cut Out Size	Φ108MM (4-1/4")
Beam Angle	°40
CRI	>90
Color Temperature(K)	2700K,3000K,3500K,4000K,5000K Adjustable
L70 Lifetime(Hrs)	>50,000
Voltage	120 Volts, Triac EVL Dimming %100-%10
Power Factor	>0.9
IC Rated	Yes
Air Tight	Yes
Material	Cold Forged Heat Sink/ Die-cast Trim Ring
Exterior Finish	Matte White/Black
Mounting	Recessed With Remote Junction Box, No Housing Required
Operating Temperature	-4°F to 104°F
Certificates	cETLus
Environment	Indoor Damp Location
Warranty	5 Years Limited

Dimensions

