



Helios Backlit Panel

AL Series



About	Application
<p>The Helios backlit panel offers superior performance to current edge lit technology. With no light guide plate this panel doesn't discolour over time giving you constant and even light. The lightweight body is easy to install in a T-bar ceiling, or use the surface kit to mount on drywall. With adjustable colour temperature and wattage available these panels give you flexibility to please the most demanding client.</p> <p>Ideal for</p> <ul style="list-style-type: none"> ◆ Schools ◆ Offices ◆ Community halls, ◆ Board rooms ◆ Restaurants ◆ Basements ◆ Garages 	<ul style="list-style-type: none"> ◆ > 50,000 hour LM70 lifespan ◆ 120-347 Operating voltage ◆ CRI >80 for true colour rendering ◆ 0-10V Dimmable ◆ Colour temperature adjustable. Static colour is available. ◆ Adjustable wattage. Static wattage is available. ◆ 120° beam angle ◆ Ambient working temperature from -20°C to 45°C ◆ Surface kits available for dry wall installation. ◆ Non flicker ◆ 5 year warranty

Specifications

Adjustable

Model	Watts	CCT	Lumens
Panel-REC-AL-BL-2x4	ADJ: 25W-30W-40W-45W-50W	ADJ: 3500K-4100K-5000K	3,250-6,500
Panel-REC-AL-BL-2x2	ADJ: 20W-25W-30W-35W-40W	ADJ: 3500K-4100K-5000K	2,600-5,200
Panel-REC-AL-BL-1x4	ADJ: 20W-25W-30W-36W-40W	ADJ: 3500K-4100K-5000K	2,600-5,200

Static

Model	Watts	CCT	Lumens
Panel-REC-AL-BL-2x4	50W	3000K/4000K/5000K	6,500
Panel-REC-AL-BL-2x2	36W	3000K/4000K/5000K	4,680
Panel-REC-AL-BL-1x4	30W	3000K/4000K/5000K	3,900

Please have the following information available when ordering

Panel-REC-BL-AL-XxX-XXX-XXXX

Panel-REC-BL-AL	__x__	_____	_____
------------------------	-------	-------	-------

X_____

Product	Size	Wattage	CCT
Panel-REC-BL-AL	2x2	ADJ	ADJ
	2x4	30W	3000K
	1x4	35W	4000K
		50W	5000K

Surface Kit
2x2
2x4
1x4



**If you have any questions
Please call or visit our showroom**

All products should be installed by a qualified technician in
accordance with the Canadian Electrical Code

