



The Leviton Load Center

The Future Made Current

LOAD CENTERS | 1-phase, 3-wire, 120/240 VAC, 22kA short-circuit rating (Canadian Market)

NEMA 1 - Indoor



Amp Rating	# of Spaces/ Circuits	Standard Door	Door with Observation Window
Main Breaker Factory Installed			
100	20	LP210-CBD	LP210-CBW
125	20	LP212-CBD	LP212-CBW
100	30	LP310-CBD	LP310-CBW
150	30	LP315-CBD	LP315-CBW
200	30	LP320-CBD	LP320-CBW
100	42	LP410-CBD	LP410-CBW
125	42	LP412-CBD	LP412-CBW
150	42	LP415-CBD	LP415-CBW
200	42	LP420-CBD	LP420-CBW
225	42	LP422-CBD	LP422-CBW
200	66	LP620-CBD	LP620-CBW
225	66	LP622-CBD	LP622-CBW
Main Lugs Only			
125	20	LP212-CLD	LP212-CLW
200	30	LP320-CLD	LP320-CLW
225	42	LP422-CLD	LP422-CLW
225	66	LP622-CLD	LP622-CLW



NEMA 3R - Outdoor

Amp Rating	# of Spaces/ Circuits	Catalog Number
Main Breaker Factory Installed		
100	20	LP210-C3B
125	20	LP212-C3B



Meter-Load Center Combination, All-in-one, UG/OH Service Entrance, EUSERC

Amp Rating	# of Spaces	Catalog Number	Bypass	Cover
150	30	LP315-MC	None	Ring Type
200	30	LP320-MC	None	Ring Type
200	42	LP420-MC	None	Ring Type

MAIN CIRCUIT BREAKERS | Hydraulic-magnetic trip, 120/240 VAC, 22kA short-circuit rating



Amp Rating	2-Pole
100	LM100
125	LM125
150	LM150
200	LM200
225	LM225

BRANCH CIRCUIT BREAKERS | Hydraulic-magnetic trip, 120/240 VAC, 10kA short-circuit rating*

Standard



Amp Rating	1-Pole	2-Pole
15	LB115	LB215
20	LB120	LB220
25	LB125	LB225
30	LB130	LB230
35	-	LB235
40	-	LB240
45	-	LB245
50	-	LB250
60	-	LB260
70	-	LB270
80	-	LB280
90	-	LB290
100	-	LB200
110	-	LB211
125	-	LB212



Catalog Number	Description
LDATA	Smart Breaker Data Hub

Using a Wi-Fi® or Ethernet connection, the LDATA Smart Hub collects data from smart circuit breakers and transmits it securely to the router

Smart Standard



Amp Rating	1-Pole	2-Pole
15	LB115-S	LB215-S
20	LB120-S	LB220-S
25	LB125-S	LB225-S
30	LB130-S	LB230-S
35	-	LB235-S
40	-	LB240-S
45	-	LB245-S
50	-	LB250-S
60	-	LB260-S
70 - 125	-	LSBMA**

**Smart Breaker Metering Accessory; CT-based design, cannot remotely update or trip breaker



AFCI



Amp Rating	1-Pole
15	LB115-AF
20	LB120-AF



Smart AFCI

Amp Rating	1-Pole
15	LB115-AS
20	LB120-AS

AFCI/GFCI - Dual Function



Amp Rating	1-Pole
15	LB115-DF
20	LB120-DF



Smart AFCI/GFCI - Dual Function

Amp Rating	1-Pole
15	LB115-DS
20	LB120-DS

GFCI - 5 mA Ground Fault Protection of Personnel



Amp Rating	1-Pole	2-Pole
15	LB115-GF	LB215-GF
20	LB120-GF	LB220-GF
25	LB125-GF	LB225-GF
30	LB130-GF	LB230-GF
40	-	LB240-GF
50	-	LB250-GF
60	-	LB260-GF



Smart GFCI - 5 mA Ground Fault Protection of Personnel

Amp Rating	1-Pole	2-Pole
15	LB115-GS	LB215-GS
20	LB120-GS	LB220-GS
25	LB125-GS	LB225-GS
30	LB130-GS	LB230-GS
40	-	LB240-GS
50	-	LB250-GS
60	-	LB260-GS

GFPE - 30 mA Ground Fault Protection of Equipment



Amp Rating	1-Pole	2-Pole
15	LB115-EP	LB215-EP
20	LB120-EP	LB220-EP
25	LB125-EP	LB225-EP
30	LB130-EP	LB230-EP
40	-	LB240-EP
50	-	LB250-EP
60	-	LB260-EP



Smart GFPE - 30 mA Ground Fault Protection of Equipment

Amp Rating	1-Pole	2-Pole
15	LB115-ES	LB215-ES
20	LB120-ES	LB220-ES
25	LB125-ES	LB225-ES
30	LB130-ES	LB230-ES
40	-	LB240-ES
50	-	LB250-ES
60	-	LB260-ES

*Series Rated 22kA with Leviton Main Breaker; see Series Ratings Tables for additional Ratings

BRANCH CIRCUIT BREAKERS | Thermal-magnetic trip, 120/240 VAC, 10kA short-circuit rating*

Standard



Amp Rating	1-Pole	2-Pole
15	LB115-T	LB215-T
20	LB120-T	LB220-T
25	LB125-T	LB225-T
30	LB130-T	LB230-T
35	-	LB235-T
40	-	LB240-T
45	-	LB245-T
50	-	LB250-T
60	-	LB260-T

*Series Rated 22kA with Leviton Main Breaker; see Series Ratings Tables for additional Ratings

AFCI



Amp Rating	1-Pole
15	LB115-AFT
20	LB120-AFT

AFCI/GFCI - Dual Function



Amp Rating	1-Pole
15	LB115-DFT
20	LB120-DFT

GFCI - 5 mA Ground Fault Protection of Personnel



Amp Rating	1-Pole
15	LB115-GFT
20	LB120-GFT
25	LB125-GFT
30	LB130-GFT

GFPE - 30 mA Ground Fault Protection of Equipment



Amp Rating	1-Pole
15	LB115-EPT
20	LB120-EPT
25	LB125-EPT
30	LB130-EPT

ACCESSORIES

Locking & Latching Devices



Description	Catalog Number
Handle padlock device for branch circuit breakers	LBHPL
Handle padlock device for main circuit breakers	LMHPL
Door locking latch kit for indoor load centers	LDRLK
Door latch kit without lock for indoor load centers	LDRLA

Outdoor & Meter Combination Load Center Accessories



Description	Catalog Number
Conduit hub, 1"	LHUB1
Conduit hub, 2"	LHB02
Conduit hub, 2 1/2"	LHUB2
Closing plate	LCLPT
5th Jaw	L5JAW
5th Jaw with neutral	L5JAW-N
Ground connector	LGDMC
Sealing ring	LRING

Lugs, Ground and Neutral Bar Kits



Description	Catalog Number
Field-installable main lugs, 3 - 300	LL630
Ground lug, 6 - 2/0	LLGND
Neutral lug, 6 - 300	LLNTL
Phase/neutral load side lug, 14 - 4	LLPHN
Ground bar kit, 11 positions, 14 - 4	LGBKT
Neutral bar kit, 14 - 1/0	LNBKT
Neutral Lug, 4 - 2/0	LL420



Miscellaneous

Description	Catalog Number
Manual transfer interlock kit	LITLK
Angle iron bracket for flush mount load centers	LBRKT
Circuit Identification Sticker (qty. 5)	LSTIK
Filler Plates (qty. 10)	LFPLT
Terminal covers for main circuit breaker	LTCVR
Bonding strap kit	LPBSK
Cover screw kit (qty. 6)	LDCKS



Leviton Manufacturing of Canada ULC

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9
Telephone: 1-800-469-7890 • FAX: 1-800-563-1853

Visit our Website at: www.leviton.com/loadcenter

© 2020 Leviton Manufacturing Co., Inc. All rights reserved.
All trademarks are the property of their respective owners.



TS-020720-tp
CDA 0620