

Hyperion

Non-Cutoff Wall Pack

TI Series







About Applications

The Hyperion LED wall pack offers maximum light for minimal power. This wall pack fits easily into existing spaces to replace high pressure sodium and metal halide. Designed for heavy outdoor use, this is ideal for parking areas, wall washing and doorways.

Hyperion LED can easily be installed into almost any fixture, in an average of 15-30 minutes.


Ideal for:


- Commercial Buildings
- Parking Lots
- Wash Bays
- ♦ Farm & Rural Applications

- ♦ 50,000 hours
- ◆ CRI >75
- ♦ 120-277 & 120-347V Available
- ♦ Colour temperature 5000/5700K
- ♦ Waterproof IP65
- Reduced energy consumption by 50% as compared to HPS/MH
- ♦ Compact low profile design
- ◆ -40°C-50°C operating range
- Mercury Free
- ♦ 5 year warranty
- Button Photocell option available

Model	Wattage	ССТ	Lumens	Voltage	Options
WP-TI-90W-57K-UNV/UHV	90W	5000K 5700K	9,300- 10,350	120-277V 120-347V	Photocell
WP-TI-120W-57K-UNV/UHV	120W	5000K 5700K	12,000-13,800	120-277V 120-247V	Photocell

Light Distribution





When ordering please specify

WP-TI-XXW-XXK-XXXV

WP-TI				
-------	--	--	--	--

	Wattage	сст	Voltage	Options
TWP-TI			UNV=120-277V UHV= 120-347V	P= Photocell

If you have any questions Please call or visit our showroom

All products should be installed by a qualified technician in accordance with the Canadian Electrical Code

