



Hyperion

T8 LED Retrofit

ZS Series



About

Hyperion LED retrofit tubes are an ideal solution for customers who currently have fluorescent lighting in their building and wish to retain the current fixtures, but are looking to improve efficiency and light output.

By installing Hyperion LED, customers slash their energy costs by 50% and at the same time increase light levels by 40%, 50% and sometimes 60%.

Hyperion LED's lead the way in energy efficiency and boast the highest lumens per watt ratings in the industry (120-150). Better efficiency means more light less money, and longer life. High CRI for extremely accurate colour representation.

Hyperion LED can easily be installed into almost any fixture, in an average of 15-30 minutes.

Available in 2Ft, 3Ft, 4Ft, and 8Ft

Ideal for:

- ◆ Offices
- ◆ Parkades
- ◆ Residential

Applications

- ◆ High output 120-150 LPW
- ◆ Reduce energy cost up to 55%
- ◆ Reduce maintenance costs up to 80%
- ◆ 60,000 to 100,000 hour lifespan
- ◆ DLC and CuL listed
- ◆ Meets CSA guidelines for certified LED retrofit applications
- ◆ No ballast required, needed or wanted
- ◆ Instant on
- ◆ T8 and T12 Retrofits
- ◆ G13, FA8 and R17D Pin configurations
- ◆ Colour temperature 3000K/4000K/5000K
- ◆ Internal or external driver
- ◆ Beam angle 130°- 160°
- ◆ Rotatable end caps
- ◆ 5 year warranty

Specifications

24" & 36" Models	Wattage	CCT	Lumens	Voltage	Wiring	Pin
T8-2FT-ZS-9W-XXK-XXXV	9W	3000K 4000K	1125-1215	100-277V	Single End Power Type B	G13
T8-3FT-ZS-10W-XXK-XXXV	10W	3000K 4000K	1250-1350	100-277V	Single End Power Type B	G13
48" Models	Wattage	CCT	Lumens	Voltage	Wiring	Pin
T8-4FT-ZS-12W-XXK-XXXV	12W	3000K 4000K	1500-1620	100-347V	Single End Power Type B Double End Power Type B	G13
T8-4FT-ZS-18W-XXK-XXXV	18W	3000K 4000K	2250-2430	100-347V	Single End Power Type B	G13
T8-4FT-ZS-22W-XXK-XXXV	22W	3000K 4000K 5000K	2750-2970	100-347V	Single End Power Type B	G13
96" Models	Wattage	CCT	Lumens	Voltage	Wiring	Pin
T8-8FT-ZS-40W-XXK-XXXV	40W	4000K	5000-5400	100-347V	Double End Power Type B	FA8
T8-8FT-ZS-40W-XXK-XXXV	40W	4000K	5000-5400	100-277V	Double End Power Type B	R17D

When ordering please specify

T8-XFT-XXW-XXK-XXXV

T8	Length	Wattage	CCT	Voltage	Type	Pins
T8	2	9	30K= 3000K 40K=4000K 50K=5000K	120-277 120-347	SEB=Single End Power Type B DEB=Double End Power Type B	G13 FA8 R17D
	3	10				
	4	12				
	8	18				
		22				
		40				

**If you have any questions
Please call or visit our showroom**

All products should be installed by a qualified technician in
accordance with the Canadian Electrical Code

